



FIBERGLASS-FREE RELEASE SHEET™
CROSSFILM® RELEASE SHEET
NSF® CERTIFIED

NON-STICK RELEASE SHEET MADE WITHOUT FIBERGLASS FOR ALL CLAMSHELL-TYPE GRILLS

FIBERGLASS-FREE RELEASE SHEET™ PROPERTIES

	2102 (SEARING)	2103 (RUGGED)	2105 (HEAVYWEIGHT)
Max Temperature:	550°F (287°C) Continuous Service		
Overall Weight oz/yd² (g/m²):	3.75 (127)	5.2 (176)	8.0 (272)
Thickness in (mm):	0.002 (0.05)	0.003 (0.08)	0.005 (0.13)
Width in (mm):	Up to 64 (1625)		
Tensile Strength lbs/in (N/50 mm):	13 (114)	20 (177)	30 (263)
Tear Strength lbs (N):	12 (53)	17 (75.6)	28 lbs (124.5)
NSF® Certified:	Yes; NSF /ANSI 4-2025		
FDA Compliance:	Yes; FDA Standard 21 CFR 177.1550		
Fiberglass-Free:	Yes		
Customizable:	Yes; sizes , shapes, and loops		



WEBSITE



TCI COOKWARE



CATALOG