



SILCOVER™ 32 Insulation Jacketing Material

SILICONE/FIBERGLASS COMPOSITES ENGINEERED FOR REMOVABLE INSULATION SERVICE

SILCOVER™ 32 Description:

This silicone/fiberglass composite with a proven flexible coating is engineered for standard duty insulation jacketing applications. With great tear, puncture and abrasion resistance, it is liquid repellent, flame retardant and easily sewn. .

- Severe chemical and temperature exposure capabilities
- Flame-resistant
- Flexible
- Easily sewn
- Economical and widely available



- Standard Colors: Silver, Dark Gray & Black

SILCOVER™ 32 PROPERTIES

Upper Use Temperature:	480°F (249°C) Continuous Service
Weight:	32.0 oz/yd ² (1085 g/m ²)
Thickness:	0.030" (0.76 mm)
Width:	60" (1524 mm) Nominal
Tensile Strength (Warp):	450 lbs/in (3938 N/50 mm)
Tensile Strength (Fill):	365 lbs/in (3194 N/50 mm)

Silcover™ is a trademark of TEXTILES COATED INTERNATIONAL. Patents worldwide This information is supplied in good faith and is based on information currently available. TCI makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

TEXTILES COATED INTERNATIONAL | Manufacturer of High-Performance Fluoropolymer Films, Laminates, and Composites

200 Bouchard Street, Manchester, NH 03103 USA PHONE: (603) 296-2221 FAX: (603) 296-2248 www.textilescoated.com