




# SILVERJAC™ 3200 Insulation Jacketing Material

SILICONE/FIBERGLASS COMPOSITES ENGINEERED FOR REMOVABLE INSULATION SERVICE

## **SILVERJAC™ 3200 Description:**

This silicone/fiberglass composite with a proven flexible coating is engineered for heavy duty insulation jacketing applications.

- **Successfully used in insulation jacketing service since 1985**
- **Incorporates proven SILVERJAC coating technology**
- **Severe chemical and temperature exposure capabilities**



**Product Close-up**

- **Variations available upon request**
- **Flame-resistant**
- **Easily sewn**

## **SILVERJAC™ 3200 PROPERTIES**

<b>Upper Use Temperature:</b>	480°F (249°C) Continuous Service
<b>Weight:</b>	34.0 oz/yd <sup>2</sup> (1153 g/m <sup>2</sup> )
<b>Thickness:</b>	0.030" (0.76 mm)
<b>Width:</b>	60" (1524 mm) Nominal
<b>Tensile Strength (Warp):</b>	425 lbs/in (3719 N/50 mm)
<b>Tensile Strength (Fill):</b>	360 lbs/in (3150 N/50 mm)

SILVERJAC is a trademark of **TEXTILES COATED INTERNATIONAL**. Patents worldwide This information is supplied in good faith and is based on information currently available. **TCI** makes NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTIES FOR FITNESS, OR USE FOR A PARTICULAR PURPOSE, OR OF ANY MERCHANTABILITY OR AGAINST INFRINGEMENT OR THE LIKE, unless expressly set forth herein.

TEXTILES COATED INTERNATIONAL | Manufacturer of High-Performance Fluoropolymer Films, Laminates, and Composites

200 Bouchard Street, Manchester, NH 03103 USA PHONE: (603) 296-2221 FAX: (603) 296-2248 www.textilescoated.com